



Performance beyond the ordinary for every office

The C610 stands out from the rest delivering fast, versatile and affordable in-house A4 colour and mono printing for the general office. With class-leading media handling, that allows you to get more from your investment, and environmental benefits, that can reduce your organisations print related carbon footprint, this powerful printer is the ultimate solution for every small to medium business. It effortlessly supports workgroups of up to 10 users

Tackle the toughest deadlines

The C610 is built for speed making light work of the toughest deadlines.

- Outstanding print speeds of 34ppm in colour and 36ppm in black and white
- Delivering your first print in as little as 9 seconds colour and 8 seconds mono
- Ultra-reliable digital LED technology with fewer moving parts and a flat paper path

Print on the paper you want

Exceptional media flexibility means that business stationery, banners and marketing collateral are just as easy to print in-house as ordinary office documents.

- Prints on stock of up to 250gsm - heavier than any comparable printer
- Handles any size from A6 to A4 through to a 1.2 metre A4 banners
- With 2 optional paper trays available, paper capacity can be increased up to 1,460 sheets

Environmental efficiencies

The C610's significantly low power consumption reduces energy bills and your environment impact.

- Low energy consumption, consuming just 1.2 watts in sleep mode
- Duplex printing (optional on C610n) reduces unnecessary paper usage and therefore costs
- Energy Star qualified products

Reduce and control your print costs

Taking care to keep costs to a minimum the C610 has an attractive price tag, high-yield toners and a long life image drum. What's more, included in-the-box, are three cost and time saving utilities. No other colour printer offers so much for so little.

- Print Control software lets you track printer usage and control costs
- PrintSuperVision software lets you monitor, manage and report on your networked printers
- Colour Access Policy Manager lets you monitor and control colour usage for printed output

A4	✓
Range of media handling	✓
Colour, mono	✓
Print	✓
Up to 10 users	✓

Variants available:

C610n
networked
C610dn
duplex, networked
C610dtn
duplex, 2nd tray,
networked



C610 - Colour and Mono Printers

PRINTER	
Print speed	A4: 34ppm colour, 36ppm mono
Time to first print	9 seconds colour, 8 seconds mono
Warm up time	up to 60 seconds from power on & up to 35 seconds from power save
Processor speed	533MHz
PRINT QUALITY	
Resolution	ProQ2400 Multi-level technology, 1200 x 600dpi, 600 x 600dpi
Enhancements	Auto Colour Balance, Photo Enhance via driver (excludes Mac and PostScript drivers)
INTERFACE AND SOFTWARE	
Connectivity	Hi-Speed USB & 10/100-TX Ethernet
Printer languages	PCL 6 (XL3.0) and PCL5c, PostScript 3 (emulation), SIDM (IBM-PPR, EPSON-FX), PDF Direct Print v1.7, XPS
Network & protocols	All major network protocols supported via ethernet card with internal web server for printer and network card set-up and management. TCP/IP: ARP, IPv4/v6, ICMPv4/v6, TCP, UDP, LPR, FTP, TELNET, HTTP(IPP), BOOTP, DHCP, SNMPv1/v3, DNS, DDNS, UPnP, Bonjour, WINS, SSL/TLS, SMTP, POP3, SNT, WSDPrint, JetDirect protocols. NetBIOSoverTCP, NetWare 3.x, 4.x, 5.x and 6 with full NDS and NDPS support:- PServer, RPrinter, NDPS supported via dedicated OKI NDPS Gateway. AppleTalk:- ELAP, AARP, DDP, AEP, NBP, ZIP, RTMP, ATP, PAP. NetBEUI:- SMB, NetBIOS. Other:EAP
OS Compatibility ¹	Windows 2000 / XP Home / XP Professional / XP Professional x64 / Server 2003 / Server 2003 for x64 / Server 2008 / Server 2008 x64 / Vista (32-bit) / Vista (64-bit); Mac OS X 10.3.9 - 10.6.1
Advanced networking and security	IPv6, 802.1x authentication, SNMPv3, SSL/TLS HTTPS encryption, Secure Print ² , Secure Erase ³ , Data encryption ³ , MAC filtering, IP filtering, IPsec
Utility Suite ¹	Color Correct, OKI LPR ² , PrintSuperVision.net ² , Swatch Utility, Template Manager ² , Web Driver Installer ² , Print Control Server ² , Print Control Client, Storage Device Manager ^{2,3} , Gamma Utility, Profile Assistant ³ , Colour Access Policy Manager ²
PAPER HANDLING	
Paper capacity	Tray 1: 300 sheets of 80gsm; Multi-purpose tray: 100 sheets of 80gsm
Paper capacity optional trays	Tray 2: 530 sheets of 80gsm (standard on C610dtn); Tray 3: 530 sheets of 80gsm
Maximum paper capacity	1,460 sheets of 80gsm
Paper sizes	Tray 1: A4, A5, B5, A6; Tray 2/3: A4, A5, B5; Multi-purpose tray: A4, A5, B5, A6, 10 Envelopes (Com-9, Com-10, DL, Monarch, C5), Labels (Avery 7162, 7664, 7666), Custom Size (up to 1,200mm length including banner); Duplex: A4, A5, B5, Custom Size: Width 148-215.9mm x Length 210-355.6mm
Paper weight	Tray 1/2/3: 64-220gsm; Multi-purpose tray: 64-250gsm; Duplex: 64-120gsm
Duplex	Standard: C610dn & C610dtn; Optional: C610n
Paper output	250 sheets face down, 100 sheets face up, 80gsm

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI Printing Solutions toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.

¹ Check local OKI Printing Solutions website for latest driver releases and OS compatibility; ²Windows only; ³SDHC Memory Card required; ⁴Including all consumables;

⁵ Secure Digital High Capacity (SDHC) Memory Card supports up to 32GB. OKI is not responsible for any compatibility risk using non-OKI genuine SDHC Memory Cards.

TYPEFACES	
Printer fonts	Scalable: 87 PCL fonts and 136 PostScript fonts; PCL Bitmap fonts. OCR-A/B; USPS ZIP Barcode
Barcode	Barcode with Checksum support

GENERAL FEATURES	
Memory	Standard RAM: 256MB; Maximum RAM: 768MB; Optional SDHC Memory Card ⁵ : 16GB
Operating conditions	Temperature/Humidity: 10°C to 32°C (17°C to 27°C recommended) / 20% to 80% RH (50% to 70% RH recommended)
	Storage: -10°C to 43°C, 10% to 90% RH
Power supply	Single phase 220-240VAC, frequency 50/60Hz +/-2%
Power consumption	Typical: 600W; Max: 1300W; Idle: 100W (average); Power Save: <15W; Sleep: 1.2W
Noise level	Operating: 54dB(A); Standby: 37dB(A); Power save: Background Level
Dimensions (HxWxD)	C610n: 340 x 435 x 546 mm; C610dn: 340 x 435 x 604 mm; C610dtn: 476 x 435 x 604 mm
Weight ⁴	C610n: 26kg; C610dn: 29kg; C610dtn: 35kg
Duty cycle	Maximum: 75,000 pages/month; Average: 1,500 to 5,000 pages per month
Warranty	Pan European 1 year on-site
Product order numbers	C610n: 44205303; C610dn: 01268901; C610dtn: 01269002

ACCESSORIES (ORDER NUMBERS)	
2nd paper tray	44274502 (standard on C610dtn)
3rd paper tray	44274502
Duplex	01272601
Cabinet	01219302
Memory	256MB: 01182907; 512MB: 01182908
SDHC Memory Card ⁵	16GB: 01272701

CONSUMABLES (ORDER NUMBERS)	
Toner cartridges* (8,000 black & 6,000 colour pages)	Cyan: 44315307; Magenta: 44315306; Yellow: 44315305; Black: 44315308
Image drum** (20,000 pages)	Cyan: 44315107; Magenta: 44315106; Yellow: 44315105; Black: 44315108
Transfer Belt (60,000 pages)	44341902
Fuser Unit (60,000 pages)	44289103

*Toner: A4 pages yield compliant with ISO/IEC 19798. Printer shipped with 2,000 A4 pages.

**Drum: A4 pages average life.

